

# CONTINUING WHERE OTHERS STOP.

The mobile fine shredders of the AK series are the ideal solution for compost or waste wood processors, disposal companies or the operators of biogas plants. Regardless of whether you process waste wood, RDF, offcuts, green waste, biowaste, manure or pre-shred tree roots, the load-sensing infeed ensures a high throughput with maximum efficiency.

You can easily combine the AK series with a preshredder or a drum screening machine. This results in a powerful complete solution for mechanical/biological treatment, biomass or refuse-derived fuels.





#### SMART SHREDDING WITH OUR GRINDER LINE.

#### RUGGED SYSTEMS.

All machines of Doppstadt's GRINDER LINE shred efficiently and reliably. They can handle substantial foreign objects, easy-to-use and easily accessible. That minimizes your maintenance costs and the downtimes on your machine. If you are not able to solve a problem on your own, Doppstadt Service will be on site in no time at all.

#### PROFITABLE RESULTS.

With the AK series, you can make your recycling processes efficient and profitable thanks to its great adaptability and mobility. The high throughput speeds up the flow of materials so that you are able to complete your jobs quickly. The processed materials are available in high quality for sale or for thermal utilization.

AK series with waste wood as example



#### VERSATILITY IN USE.

Like all Doppstadt machines, the models of the AK series can be expanded and are thus very versatile. Every machine can be precisely configured to your requirements. For instance, you can adapt the shredding system, selecting an additional removal of the FE-fraction at the rear conveyor or increasing the hopper's capacity in order to be able to feed more material per loading cycle. If you choose a model equipped with a track-laying chassis, the machine is sure-footed and safe even over rough terrain.



### WE HAVE LISTENED TO YOU CAREFULLY.

From ease of maintenance and increased performance through to new decentralized electrical system, we have further developed the AK series in accordance with your requirements. It is the special solutions from Doppstadt that help you and make your work better every day.

#### **FOOT SWITCHES ENSURE** SAFE OPERATION.

To be able to operate the AK even more efficiently, you can optionally equip your shredder with foot switches for the radio remote control. On the one hand, this enables the AK to move forward, for instance, when creating compost windrows, and on the other hand, to manually reverse the infeed.

The use of foot switches is especially reasonable when you need to maintain full control over demanding materials. Both hands remain free. And you can fully concentrate on controlling the loading vehicle.

#### 1 EFFECTIVE COOLING

The fan's speed is controlled intelligently, and the engine compartment is optimally cooled with fresh air. Long periods of use are not a problem thanks to the fan's reverse feature. In addition to that, the swivelling cooler is easy to access for further maintenance.

#### 2 POWERFUL ENGINE PERFORMANCE

The new EU Stage V engines deliver a higher torque. For maximum service life, the supercharged air / air intake piping, the exhaust system and the AGN box are made entirely of stainless steel and are insulated.

#### **3** EASY TO USE

The central multifunctional display is used to configure the machine and monitor the data. You can control the AK easily using the remote control while sitting on the loading vehicle.

#### **4** FULL MOBILITY

Thanks to the optional hydraulic drive, you can simple move the wheeled machine to create, for instance, a compost windrow.

#### 5 EFFICIENT DRIVE TRAIN

Hydraulically supported, the drive belt remains at an ideal tension even when the loads change. As a result, the power is efficiently transferred from the engine to the flail drum, significantly reducing the wear and tear on the drive train.

#### 6 UNIFORM FLOW OF MATERIAL

Scraper floor and infeed roller draws the material into the shredding unit evenly. This allows you to work without tiring even on long days.





# MORE THROUGHPUT WITH THE TWIN DRIVE.\*

- Continuous shredding: The control of the material infeed is load-sensing.
- Increased throughput: You are able to process more material per liter of fuel.
- Uniform flow of material in every application: The scraper floor and infeed roller can be adjusted independently of the speed.
- Reduced workload in daily routine: The machine reverses automatically and in relation to output load.
- High reliability and easy maintenance:
   You do not have to control the chain drive.



#### 7 LESS DUST

The damping facility (optional) significantly reduce occurrence of dust if necessary.

#### 8 MAXIMUM GRNDING PERFORMANCE

The large-sized flail drum with its flywheel mass of approx. 2.5 m. ton and free-swinging flail tips shred materials thanks to their high impact power.

The rugged rotor can easily handle even substantial foreign materials. The baffle plate in different configurations supports the shredding process adapted to your applications.

#### 9 PRECISE FINE SHREDDING

You can determine the desired size of the output material with the aid of fine-shredding baskets, which have a mesh size between 30 and 400 mm.

#### 10 FAST REFITTING

The rear conveyor, which can be lowered to the ground, (optional) ensures quick access for maintenance and refitting. A neodymium magnetic pulley that can be optionally integrated in the conveyor and an overbelt magnet removes FE metals from the material.

#### SMART CONNECTION.

With the cloud-based Doppstadt telematics solution, you can keep an eye on your system at all times. The system provides you with all machine parameters in real time via GPS.

### REDUCING UNNECESSARY DOWNTIME.

All models of the AK series are equipped with large doors and maintenance hatches, making routine maintenance much easier for your operators and workshop technicians. You will be impressed by how quickly your machine is ready to operate again.

For instance, the machine's rear conveyor can be lowered almost completely to the ground (optional). This means that not only is the flail drum easy to access but also also the tools, baffle plates and shredding baskets. The baskets can be replaced within only 15 minutes.



"The flail tips can be quickly changed on site. This makes my daily work on the machine easier."

(Michael Steffen, Application Engineer at Doppstadt Calbe GmbH)

#### **REMOTE DIAGNOSIS SAVES** VALUABLE TIME.

Providing world-class service means: Wherever you are working, we are at your side. The AK series has telematics monitoring and remote diagnostics systems.

As a result, Doppstadt service technicians can quickly assist you with malfunctions or repairs - even without always having to be on site themselves.








## YOU WORK MORE EFFICIENTLY WHEN EVERYTHING SUITS YOUR NEEDS.

The more precisely your tool matches the material, the more convincing the work result. In the AK series, you will find extensive equipment options, with which you can adapt your machine exactly to the operating conditions. Choose from a wide variety of flail tips, rear baskets and deflector plates. Green waste in the morning, waste wood in the afternoon – you can switch to the right basket in no time at all.



#### SHREDDER EQUIPMENT OPTIONS

#### 1 SHREDDING BASKET **2** BAFFLE PLATE 3 FLAIL DRUM 4 FLAIL TIP ■ Diamond rear basket: ■ Toothed ■ For AK 315: ■ Chisel ■ Carbide Plus Different mesh sizes ■ Counter blade fixed teeth, from 30 to 400 mm ■ Counter blade reinforced freely oscillating flails, ■ Bear paw with HM new additional ■ Strip basket: ■ Smooth ■ Bear paw with HM 2R specifically for green waste ■ Counter blade with hard surfacing ■ Rear basket 3D waste wood: row of teeth ■ As of AK 565: specifically for waste wood, freely oscillating different mesh sizes flails from 80 to 300 mm ■ Rear basket 3D mulch: specifically for small particle sizes, for waste wood and biomass. different mesh sizes from 50 to 100 mm



#### FREQUENTLY IMITATED. NEVER MATCHED.

The flail drum forms the heart of the machine. The sophisticated and unique shredding principle of the flail drum enables you to break down the material to a particular high degree. Ferrous parts are cleanly separated from the waste wood, the composting of green waste is significantly accelerated.



# YOU WILL FIND EXACTLY THE RIGHT MACHINE.

In the AK series, you will find the machine that meets your high standards. The mobile, high-speed shredders are available in different sizes and performance dimensions. Our experts will be happy to advise you to ensure that you have the machine that suits your recycling requirements at your disposal. The range extends from the smallest, high-performance shredder AK 315, the all-purpose shredder AK 565 through to the flagship AK 640 SA, which you can use to move mountains day after day.



#### **GRINDER LINE**



AK 315
The compact for more perspectives in recycling.

### 2

## **AK 565**The capable contractor for more performance – even mobile.



3

#### AK 640 K

The colossus for powerful performance even off-road.





3

#### AK 640 SA

The mobile flagship for really major jobs.





**2 AK 565 K**The offroader for full throughput off the beaten path.

## 2 AK 565 PLUS The flexible for more va

The flexible for more variety of features.



## PERFORMANCE PARAMETERS

- Small material streams up to 35,000 m. ton/yr
- Average material streams up to 60,000 m. ton/yr
- Large material streams up to 90,000 m. ton/yr

"Large, powerful and still mobile. The AK 640 SA is unstoppable, just like its smaller sibling, which shares many technical refinements with the flagship."

(Jan Hauschild, Project manager, Doppstadt)

Learn more about Doppstadt's solutions and their advantages.



Exhaust system



Hydraulic



Control system



	AK 565	AK 565 K
2-axle trailer	2-axle trailer	Track-laying chassis
16,000 kg	19,000 kg	29,000 kg
12,890 mm	11,780 mm / 13,250 mm	13,750 mm
2,130 mm	2,500 mm	3,000 mm
3,550 mm	3,000 mm / 4,150 mm	5,090 mm / 5,290 mm (with off-road chassis)
9,240 mm	9,770 mm / 9,850 mm	8,670 mm
2,130 mm	2,500 mm	3,000 mm
3,080 mm	3,960 mm / 3,850 mm	3,390 mm / 3,500 mm (with off-road chassis)
Diesel	Diesel	Diesel
MTU 6R 1000	MTU 6R 1300	MTU 6R 1300
Stage V / EPA Tier 4f / EIIIA	Stage V / EPA Tier 4f / EIIIA	Stage V / EPA Tier 4f / EIIIA
230 kW/310 HP	390 kW/530 HP	390 kW/530 HP
1,300   1,250 (EIIIA) at 1,200-1,600 rpm	2,600   2,460 (EIIIA) at 1,300 rpm	2,600   2,460 (EIIIA) at 1,300 rpm
300 L	450 L / 600 L* * Optional.	600 L
16/28	36	36
1,470 mm	1,750 mm	1,750 mm
		1,120 mm
1,140-1,320 rpm (depending on the engine's speed)	850-1,000 rpm (depending on the engine's speed)	850-1,000 rpm (depending on the engine's speed)
401	570	570
		538 mm
2,050 mm	2,180 mm	2,670 mm 2,230 mm / 2,430 mm (with offroad chassis)
		(With Official Chassis)
6,000 mm	4,000 mm / 6,000 mm* * Optional.	7,500 mm
1,500 mm	1,800 mm	1,500 mm
2 m/s	2 m/s	2 m/s
3,550 mm	3,000 mm / 4,150 mm* * Optional.	5,090 mm
Hydraulic drive, overbelt magnet, neodymium magnet pulley, damping facility, dust and noise suppression hood, central lubrication, hopper extensions, scraper floor chain lubrication, winter package, LED light kits	Hydraulic drive, overbelt magnet, neodymium magnet pulley, damping facility, dust and noise suppression hood, infeed roller clean EBS, central lubrication, hopper extensions, scraper floor chain lubrication, winter package, LED light kits	Overbelt magnet, neodymium magnet pulley, damping facility, dust and noise suppression hood, infeed roller clean EBS, central lubrication, hopper extensions, scraper floor chain lubrication, winter package, LED light kits
	16,000 kg  12,890 mm 2,130 mm 3,550 mm  9,240 mm 2,130 mm 3,080 mm  Diesel  MTU 6R 1000 Stage V / EPA Tier 4f / EIIIA 230 kW/310 HP 1,300   1,250 (EIIIA) at 1,200-1,600 rpm 300 L  16/28 1,470 mm 900 mm 1,140-1,320 rpm (depending on the engine's speed)  421 mm 2,730 mm 2,050 mm  Hydraulic drive, overbelt magnet, neodymium magnet pulley, damping facility, dust and noise suppression hood, central lubrication, hopper extensions, scraper floor chain lubrication, winter	12,890 mm

	AK 565 PLUS	AK 640 K	AK 640 SA
Chassis	3-axle trailer	Track-laying chassis	3-axle Semi-trailer
DIMENSIONS			
Overall weight	22,000 kg	32,500 kg	32,000 kg
WORKING POSITION			
Length	13,380 mm	15,910 mm	17,380 mm
Width	2,500 mm	3,000 mm	2,530 mm
Height	4,290 mm	5,090 mm / 5,290 mm (with offroad chassis)	5,350 mm
TRANSPORT DIMENSIONS			
Length	9,990 mm	10,020 mm	11,990 mm
Width	2,500 mm	3,000 mm	2,530 mm
Height	3,810 mm	3,390 mm / 3,590 mm (with offroad chassis)	3,650 mm
DRIVE			
Engine type	Diesel	Diesel	Diesel
Make	MTU 6R 1300	MTU 6R 1500	MTU 6R 1500
Emission standard	Stage V / EPA Tier 4f / EIIIA	Stage V / EPA Tier 4f / EIIIA	Stage V / EPA Tier 4f / EIIIA
Nominal output	390 kW/530 HP	480 kW / 652 HP 460 kW / 625 HP (EIIIA)	480 kW / 652 HP 460 kW / 625 HP (EIIIA)
Torque	2,600   2,460 (EIIIA) at 1,300 rpm	3,100   2,900 (EIIIA) at 1,300 rpm	3,100   2,900 (EIIIA) at 1,300 rpm
Tank capacity	600 L	750 L	900 L
FLAIL DRUM			
Number of flails / teeth	36	36	36
Width	1,750 mm	1,750 mm	1,750 mm
Diameter	1,120 mm	1,120 mm	1,120 mm
Speed	850-1,000 rpm (depending on the engine's speed)	970-1,140 rpm (depending on the engine's speed)	970-1,140 rpm (depending on the engine's speed)
FEED HOPPER			
Infeed height	538 mm	538 mm	538 mm
Filling width	2,670 mm	3,500 mm	5,720 mm
Loading height	2,260 mm	2,220 mm / 2,420 mm (with off-road chassis)	2,420 mm
DISCHARGE BELT	5.000	7500	7500
Length	6,000 mm	7,500 mm	7,500 mm
Width Belt speed	1,800 mm	1,500 mm	1,500 mm
Discharge height	2 m/s 4,290 mm	2 m/s 5,090 mm	2 m/s 5,350 mm
OTHER	4,230 11111	3,030 11111	3,330 11111
Optional equipment	Hydraulic drive, overbelt magnet, neodymium magnet pulley, damping facility, dust and noise suppression hood, infeed roller clean EBS, central lubrication, hopper extensions, scraper floor chain lubrication, winter package, LED light kits	Overbelt magnet, neodymium magnet pulley, dust and noise suppression hood, infeed roller clean EBS, central lubrication, hopper extensions, scraper floor chain lubrication, winter package, LED light kits	Hydraulic drive, overbelt magnet, neodymium magnet pulley, dust and noise suppression hood, infeed roller clean EBS, central lubrication, hopper extensions, scraper floor chain lubrication, winter package, LED light kits

### BEST SOLUTION. SMART RECYCLING.

Our innovative solutions have made us a leading supplier and manufacturer of processing technology. Customers in the waste disposal and recycling industry all over the world trust our expertise and benefit from our qualified service every day.

We are always there for you. At the Doppstadt Academy, we develop your team online and offline so that you can fully exploit the performance potential of the machines and make operations even more productive. Added to this are worldwide security of supply, fast on-site repair service and all-round carefree packages within service and maintenance contracts.

Because "every machine is only as good as the service behind it." (Werner Doppstadt)













